





otes:

Anchor bolts at fixed bearings may be cast into the masonry.

The cost of furnishing and installing new rocker bearings and bolsters shall be included with Furnishing and Erecting Structural Steel.

See Sheet 17 of 34 for Anchor bolt notes.

Two $^{\prime}_{8}$ in. adjusting shims shall be provided for each bearing in addition to all other plates or shims and placed as shown on bearing details.

BILL OF MATERIAL

Item	Unit	Total
Anchor Bolts, 1"	Each	9

BEARING ASSEMBLY DETAILS

AT PIERS 2 & 4

NOTES FOR SETTING OF ANCHOR BOLTS AT EXPANSION BEARINGS

a.) D^* (Side of brg. away from fixed brg.) $D^{*=}l_6$ " per each $32'-9^3{}_4$ " of expansion for every 8 °C fall below the normal temp. of 10 °C.

D*** (Side of brg. toward fixed brg.) $D^{**=}|_{6}^{e}$ per each $32'-9^{3}_{4}^{e}$ of expansion for every 8 °C rise above the normal temp. of 10 °C.

AT PIERS 1 & 3

b.) After beams have been erected and dimensions D* & D** determined, holes shall be drilled and anchor bofts shall be installed.

V3 Companies of Illinois Ltd.
7325 Janes Avenue

Waodridge, IL 60517
630.724.9202 fax

www.v3co.com

PLOT DATE: July 1, 2011

PLOT DATE: July 1, 2011

PLOT SCALE: II

PLOT DATE: July 1, 2011

PLOT SCALE: II

PLOT DATE: July 1, 2011

STATE OF ILLINOIS DEPARTMENT OF TRANSPORTATION

.I. E.	SECTION	COUNTY	TOTAL SHEETS	SHEET NO.		
4	72-6VB	PEORIA	133	61		
CONTRACT NO. 68874						
ILLINOIS FED. AID PROJECT						